



OMEGA ... ELECTRIC CONNECTION

EL. supply 230V AC 50Hz (cable 3Cx2.5), lenght of free end of eL.cable 2m, together with cable earth connecting CY6mm, green/yellow ensure customer before installation of platform.
 EL. supply must be attach individual elektr. circuit breaker 16A/C and residual current circuit breaker (RCCB) for residual sinusoidal alternating currents 0,03A, type A-G, sensitive residual pulsating direct currents

PILLAR	LENGTH	PILLAR	LENGTH
A	800	G	1250
B	1275	H	1200
C	1465	I	1335
D	1375	J	1280
E	1340	K	1230
F	1285	L	1170

Order:

POWER SUPPLY (EL. CONTROL BOX)	1x230V	EL. MOTOR:	1,1kW/3x230V	nmot=1400	1/min
GEAR BOX TYPE:			SRS50/71B14		
			z1=30, z2=130		
i	(1)		40		
n3	(1/min)		8,077		
v	(m/s)		0,09		
ROPE:	DIAMETER:9 mm	TRACTION ROPE:	8748 mm	DIAMETER:7.1 mm	SUPPORTING ROPE: 9450 mm
ROPE FIXING:	A50500-000-04	CURRENT COLLECTOR:	A50540-000-00		

1:20

**Lifte Plus Pl. Kaczmarczyk,
 Spółka Jawna, Strażacka 33
 42263 Wrzosowa k. Częstochowy, POLAND**

OMEGA